

# T8 3-POINT TRACTOR MOUNT

TimberMAX Hydraulic Power pack



## INTRODUCING THE TRACTOR 3-POINT HITCH MOUNT

### EXPANDING VERSATILITY & EFFICIENCY

We are excited to introduce the latest innovation in our winch attachment lineup - the Tractor 3-Point Hitch Mount for T8 Winches. This new addition enhances our versatile lineup, offering greater ease and flexibility for installation on a wide range of tractors. The compact design ensures that the operating weight remains low, while the inclusion of its own hydraulic power pack enhances performance and efficiency.

This kit features a high-end hydraulic power unit. The reliable Rexroth axial piston pump delivers high pressure to meet TimberMAX requirements, providing the best performances with a constant pull of up to 90 kN.



### iWINCH CONTROL SYSTEM

- ✓ User-Friendly and Intuitive
- ✓ Bi-Directional Communication
- ✓ 12" Display
- ✓ Full Diagnostic
- ✓ Data Logging
- ✓ Easy Install



### WHY SHOULD YOU CHOOSE TIMBERMAX?



#### HIGH PERFORMANCE

UP TO 9 KM/H AND UP TO 90kN CONST. PULL



#### VERSATILE & FLEXIBLE

QUICK INSTALL ON A WIDE RANGE OF CARRIER



#### 3 AUTOMATIC TENSION SETTING

UPHILL - NOT MOVING - DOWNHILL



#### STRONG & SAFE

16MM ROPE DIAMETER AND 3:1 SAFETY FACTOR



#### iWINCH REMOTE CONTROL

SAFE OPERATIONS, ALARMS & DATAS



#### QUICK AND EASY INSTALLATION

+12 OR +24V CIGARETTE LIGHTER

### Contact our Team

TimberMAX Manufacture Canada  
+1-871-771-0949  
info@timbermax.ca

TimberMAX Europe  
+43 664 4603298  
roland@timbermax.ca

TimberMAX

JOIN OUR CUMMUNITY!



# T8 3-POINT TRACTOR MOUNT

TimberMAX Hydraulic Power pack



## TRACTOR REQUIREMENTS

Horse Power	120 kW (160 PS)
Three Point Hitch Rear	CAT 3
Three Point Hitch Front	CAT 2
PTO Shaft Output	1000 rpm

## HYDRAULIC POWER PACK

Hydraulic Pump	210 cc
Hydraulic Oil Tank	220 l
Oil Cooler with Bypass	Yes
Return Filter	Yes
Drain Filter	Yes
Low Level Alarm	Yes



## TIMBERMAX WINCH T8

Wire Rope Length	340 m
Wire Rope Diameter	16 mm
Pulling Capacity at Top Layer	90 kN
Pulling Capacity at Core Layer	158 kN
Line Speed	Up to 9 km/h
Communication	Bi-Directional

## 3-POINT HITCH AND BLADE

Blade Width	240 cm
Counter Balance Valve	Yes
Cross Port Relief	Yes
Number of Cylinder	2
Overall weight with winch and powerpack	3,680 kg

## Contact our Team

TimberMAX Manufacture Canada  
+1-871-771-0949  
info@timbermax.ca

TimberMAX Europe  
+43 664 4603298  
roland@timbermax.ca

TimberMAX

JOIN OUR CUMMUNITY!

